

Magnetic Solid Door • Tested at ambient temperature of 38°C



BS 2DUC/Z



BS 4DUC/Z



BS 6DUC/Z



	2 Door	4 Door	6 Door
Model	BS 2DUC/Z	BS 4DUC/Z	BS 6DUC/Z
Temperature °C (Celcius)	+1 to +6	+1 to +6	+1 to +6
External Dimension (mm)	650 x 770 x 2060	1300 x 770 x 2060	1950 x 770 x 2060
Gross Volume (Litres)	471	1029	1602
Voltage / Frequency (V/Hz)	230V / 1 / 50Hz 220V / 1 / 60Hz	230V / 1 / 50Hz 220V / 1 / 60Hz	230V / 1 / 50Hz 220V / 1 / 60Hz
Cooling Capacity (W)	522	792	913
Wattage (W)	341 - 377	480 - 530	709 - 783
Ampere (A)	2.3 - 2.6	3.1 - 3.4	5.2 - 5.8
Refrigerant	R134a	R134a	R134a
Defrost System	Forced Air Circulation	Forced Air Circulation	Forced Air Circulation
PVC Coated Shelving	4	8	12
Weight (kg)	97	147	201
Unit for 20ft / 40ft Container	23 / 48	11 / 23	7 / 15
Top View			
Front View			

Optional : CW - Castor Wheel / BF - Bullet Fleet