

Double layer heated glass, frost free • Tested at ambient temperature of 32°C • Silver Matt Aluminium Frame



1D/DC-SM



2D/DC-SM



3D/DC-SM



Model	1 Door 1D/DC-SM	2 Door 2D/DC-SM	3 Door 3D/DC-SM
Temperature °C (Celcius)	+1 to +6	+1 to +6	+1 to +6
External Dimension (mm)	635 x (710 + 20) x 2060	1260 x (710 + 20) x 2060	1880 x (710 + 20) x 2060
Gross Volume (Litres)	400	876	1351
Voltage / Frequency (V/Hz)	230V / 1 / 50Hz 220V / 1 / 60Hz	230V / 1 / 50Hz 220V / 1 / 60Hz	230V / 1 / 50Hz 220V / 1 / 60Hz
Cooling Capacity (W)	839	1144	1694
Wattage (W)	365 - 404	599 - 662	895 - 989
Ampere (A)	2.3 - 2.6	3.3 - 3.7	4.8 - 5.3
Energy Consumption (kw/24h)	5.6 - 6.2	11.4 - 12.6	20.7 - 22.9
Refrigerant	R134a	R134a	R134a
PVC Coated Shelving	5	10	15
Auto Door Lock	Yes	Yes	Yes
Weight (kg)	95	157	209
Unit for 20ft / 40ft Container	24 / 51	12 / 27	9 / 18
Top View			
Front View			